

SafePace 475 Driver Feedback Radar Speed Sign

General Description

The SafePace 475 driver feedback sign is an 18" digit, full size radar sign. It can be mounted at multiple locations with a universal mounting bracket and can function autonomously for weeks at a time with optional battery power.

Features

- MUTCD compliant with static "YOUR SPEED" message and highly visible 18" LED digits that are visible from up to 1,000 feet away.
- User friendly software interface allows you to manage sign parameters such as threshold speeds and violator strobe remotely
- **Ultra low power consumption** including the most power-efficient radar technology available, optional solar power, and optional battery power that allows the sign to function autonomously for **up to five weeks**
- High strength aluminum sign face and individual optical lenses to protect against vandalism and theft
- Stealth Mode: Baseline traffic data can be collected for comparison and analysis while speed display appears blank to motorists.
- Speed Violator Strobe: Programmable flashing strobe alerts drivers to slow down when they exceed the threshold speed you choose.
- Universal Mounting: Optional mounting brackets let you use one sign at multiple locations with the turn of a key.
- Superior construction and durability for long-lasting performance.










Choice of faceplate colors available.

SafePace 475 Specifications

Digit Size	18"
Height	42"
Weight	42 lb.
24/7, 365 Scheduling	$\sqrt{}$
Data Collection	√
Solar Compatibility	$\sqrt{}$
Battery Operated	$\sqrt{}$
Universal Mounting	$\sqrt{}$
Cloud Compatibility	$\sqrt{}$
Trailer Compatibility	$\sqrt{}$
Hitch Compatibility	V
Warranty	2 Years





Feature	Specifications	
Dimensions		
Digits	18"(h) x 9.6"(w), 112 LEDs per digit	
Text	Letters 6.0" (h) spell "YOUR SPEED" fixed message, 2 lines	
Unit Alone	24.6"(h) x 29.5"(w) x 3.5"(d)	
Unit with "YOUR SPEED" Sign Mounted	42.0"(h) x 31.5"(w) x 3.5"(d)	
Sign Weight		
AC Powered	42 lb.	
4 Cell Battery Powered Model	53 lb. (3 batteries)	
Solar Powered Model	42 lb. (not including solar panel or bracket)	
General Specifications		
Operating Temperatures F° (C°)	-40° (-40°) to 185° (85°)	
Speed Units	Miles per hour (mph) or kilometers per hour (km/h)	
Faceplate	Yellow or white high-intensity prismatic reflective sheeting on sign face with black colored text. MUTCD approved colors and format.	
Bashplate	Aluminum, 0.1875"	
Communications	Bluetooth (standard), GSM/GPRS (optional, for use with SafePace Cloud)	
Programming	SafePace Pro sign management software, SafePace Cloud remote sign management, 24/7 365 day unlimited programming and scheduling	

Feature	Specifications	
Power Options (Electrical Specifications)		
AC Power Input	100~240 V AC	
DC Power Input	12 V DC	
Solar Panel Options	90W	
Radar		
Strobe	Dual Strobe and Single Strobe	
Internal	Doppler (FCC approved)	
Radar RF Out	5 mW maximum	
Radar F-center	24.125 GHz +/- 25 MHz	
Pickup Distance	Up to 1,200 feet	
Beam	24° (vertical) x 12° (horizontal), linear polarization	
Display		
LEDs	245	
Digits	224 Amber, 23°, 5 mm, luminous intensity (5,000 – 12,000 mcd/LED)	
Speed Violator Strobe	21 White, 15°, 5 mm, luminous intensity (18,000 – 28,000 mcd/LED)	
Optical Lenses	245	
Ambient Light Sensors	2 sensors and automatic brightness control	
Enclosure		
Construction	12 gauge aluminum, flat black powder coated front for reduced glare and maximum contrast; light gray powder coated body to minimize heat absorption	
Weatherproof Rating	Weatherproof, NEMA 4X-12, IP65 level compliant. Non-sealed and ventilated.	
Warranty		
Sign	2 years	
Batteries	1 year	

^{+1.916.394.9884} Worldwide

^{+1.916.394.2809} Fax