


SafePace 550 Variable Speed Limit Driver Feedback Radar Speed Sign

General Description

The SafePace 550 Variable Speed Limit Sign offers the flexibility to display speed limits based on work or school zone scheduling. Using highly visible LEDs, the SafePace 550 Variable Speed Limit Sign ensures that motorists are aware when the speed limit has changed. With a built-in strobe and flashing digits to warn violators, the SafePace 550 sign is ideal for use anywhere that speed limits fluctuate.

Features

- MUTCD compliant with static "SPEED LIMIT" message and highly visible 15" LED digits
- Ideal solution for locations with changing speed limits such as school or work zones
- Unique light enhancing, anti-glare lens system provides brilliant visibility even in poor lighting.
- Includes integrated flashing speed violator strobe to alert speeding drivers
- Ultra low power consumption including the most power efficient radar technology available and optional solar power
- High strength aluminum sign face and individual optical lenses to protect against vandalism and theft
- Stealth Mode: Baseline traffic data can be collected for comparison and analysis while speed display appears blank to motorists.
- Speed Violator Strobe: Programmable flashing strobe alerts drivers to slow down when they exceed the threshold speed you choose.
- Universal Mounting: Optional mounting brackets let you use one sign at multiple locations with the turn of a key.
- Superior construction and durability for long-lasting performance.






Choice of faceplate colors available.

SafePace 550 Specifications

Digit Size	15"
Height	40"
Weight	24 lb.
24/7, 365 Scheduling	
Data Collection	\checkmark
Solar Compatibility	\checkmark
Battery Operated	\checkmark
Universal Mounting	\checkmark
Cloud Compatibility	\checkmark
Trailer Compatibility	\checkmark
Dolly Compatibility	\checkmark
Hitch Compatibility	
Warranty	2 Years

xwalk.com sales@xwalk.com Traffic Safety Corp., 2708 47th Ave. Sacramento, CA, 95822, USA



Feature	Specifications	
Dimensions		
Digits	15"(h) x 8"(w), 112 LEDs per digit	
Text	Letters 6.0" (h) spell "SPEED LIMIT" fixed message, 2 lines	
Unit Alone	21.5"(h) x 26"(w) x 3.5"(d)	
Unit with "SPEED LIMIT" Sign Mounted	40.0"(h) x 30.0"(w) x 3.5"(d)	
Sign Weight (unit alone, without "SPEED LIMIT" sign)		
AC Powered	24 lb.	
4 Cell Battery Powered Model	24 lb.	
Solar Powered Model	24 lb. (not including solar panel or bracket)	
General Specifications		
Operating Temperatures F° (C°)	-40° (-40°) to 185° (85°)	
Speed Units	Miles per hour (mph) or kilometers per hour (km/h)	
Faceplate	White high-intensity prismatic reflective sheeting on sign face with black colored	
•	text. MUTCD approved colors and format.	
Bashplate		
	text. MUTCD approved colors and format.	

Feature	Specifications	
Power Options (Electrical Specifications)		
AC Power Input	100~240 V AC	
DC Power Input	12 V DC	
Solar Panel Options	50W	
Radar		
Strobe	Dual Strobe and Single Strobe	
Internal	Doppler (FCC approved)	
Radar RF Out	5 mW maximum	
Radar F-center	24.125 GHz +/- 25 MHz	
Pickup Distance	Up to 1,200 feet	
Beam	24° (vertical) x 12° (horizontal), linear polarization	
Display		
LEDs	245	
Digits	224 White, 15°, 5 mm, luminous intensity (18,000 – 28,000 mcd/LED)	
Speed Violator Strobe	21 White, 15°, 5 mm, luminous intensity (18,000 – 28,000 mcd/LED)	
Optical Lenses	245	
Ambient Light Sensors	2 sensors and automatic brightness control	
Enclosure		
Construction	12 gauge aluminum, flat black powder coated front for reduced glare and maxi- mum contrast; light gray powder coated body to minimize heat absorption	
Weatherproof Rating	Weatherproof, NEMA 4X-12, IP65 level compliant. Non-sealed and ventilated.	
Warranty		
Sign	2 years	
Batteries	1 year	

xwalk.com sales@xwalk.com Traffic Safety Corp., 2708 47th Ave. Sacramento, CA, 95822, USA



Product specifications may be subject to change without prior notice. Verify current specifications when ordering. © Traffic Safety Corp. | 1/14/2020