



Traffic Safety Corporation
 2708 47th Ave.
 Sacramento, CA 95822-3806
 Toll Free: 888.446.9255
 Tel: 916.394.9884
 Fax: 916.394.2809
 Email: sales@xwalk.com
 Web: www.xwalk.com

TS2000

Low Voltage System Controller

General Description

Traffic Safety's Low Voltage System Controller is designed to provide safe control of energy efficient LED based light fixtures. Its DC output design provides for a safer, more efficient transfer of power to LED based fixtures by eliminating the need for AC power transfer and conversion at each fixture. The low power consumption of the controller allows it to be operated from an AC power source, or from an integrated solar power supply (option). Output activation control options include: Internal on/off switch (standard), photocell, keyfob, programmable timer (options), or an external on/off switch (supplied by customer). The system is fully protected from input transients, output overload, over-voltage and over-temperature conditions. The NEMA 4 compliant enclosure with lock provides protection from adverse weather, and security from unauthorized access.

Low Voltage LED System Benefits

- **Safety**
 - Low voltage DC is inherently safer than AC controlled systems.
- **Lower Maintenance Costs**
 - Fully integrated control and power distribution system simplifies system setup and maintenance.
 - The long life expectancy of LED lamps reduces the frequency of lamp replacements.
- **Lower Power and Operating Costs**
 - Low power LED technology reduces power consumption and operating costs.
 - Solar power option utilizes free renewable energy for the utmost in long term savings and environmental friendliness.
- **Flexibility**
 - Ability to control the system operation by various means: on/off switch, photocell, keyfob, and timer.
 - With dimming option, lights can be dimmed at night to reduce glare. Three brightness levels can be selected.

Features

- Low voltage (15 VDC Output) control of LED lights.
- Solar power option available.
- Dimming option for security applications: brightness control selector allows lights to be dimmed at night to reduce glare.
- Simple operation: Internal on/off power switch.
- Optional output power capability: 150 watt (standard) or 300 watt (optional).
- 100 watt maximum output for Solar Powered version.
- Wide operating temperature range: -10°C to + 55°C.
- Input transient protection.
- Output overload and over-voltage protection.
- Over-temperature shut-down protection.



Low Voltage System Controller

Optional Keyfob Remote Control Transmitter

A wireless key fob can remotely control the TS2000.

Technical Specifications

- 433MHz signal frequency
- 600 ft. range
- 4 button dimming option: Low, Medium, High, Off
- 2 button On-Off control for non-dimmable lights.
- Highly secure, more than 16 million codes
- Water tight



Ordering Code

Product Code	Options
SC-TS2000 ¹	-2: 240V, 60Hz Powered -3: 230V, 50Hz Powered -SP: Solar Powered -H ² : 15 VDC, 300 Watt Load Limit -D ³ : Dimming CNTL -K: Keyfob Remote Control Transmitter

1. Standard System (No Options) uses internal On/Off Switch, 110 VAC Input, and provides a steady 15 VDC Output (No Dimming) limited to 150 Watts with AC power supply or 100 watts with solar option (-SP).
2. Available for systems with AC inputs.
3. Dimming CNTL provides three brightness levels.
4. Shipping dimensions: 15" x 15" x 10" (38cm x 38cm x 25cm). Shipping weight: 17 lb. (8 kg)

Enclosure Specifications

- Standard System: NEMA 4 (12"H x 10"W x 5"D) steel enclosure with security lock.
- Solar Power Option: Enclosure per customer system requirements.
- Dimming Option: NEMA 4 (14"H x 12"W x 6"D) steel enclosure with security lock.
- Keyfob Option: NEMA 4 (14"H x 12"W x 6"D) polycarbonate enclosure.

Visit our web site: www.xwalk.com