

Safe-Hit® Delineator Post

General Description

The Safe-Hit® Delineator Post is constructed of flexible and durable co-extruded polyethylene with ultraviolet inhibitors. It is self-certified as a NCHRP Report 350 and MASH Category 1 Device, and tested to NTPEP. It can be configured to MUTCD requirements for delineators or channelizing devices. The Safe-Hit® Delineator Post is ideal for roadside or lane line applications.

Assembly and Maintenance

- Lightweight delineator post.
- Two-piece, self-locking system helps reduce installation and replacement time.

Specifications

- 18" to 54" high
- 2.25" diameter
- 3" width on flattened top versions

Features

- Multiple base anchor options and portable bases.
- Surface mount bases ideal for asphalt or concrete.
- Soil anchors work in a wide range of soil types.
- Portable bases available in 18 lb and 32 lb.
- Ultraviolet (UV) resistant post.
- Round post design can provide increased visibility in up to 360° direction.
- Standard post colors: white, yellow, and orange.
- Standard reflective colors: silver, amber, and orange.
- Custom colors available.
- Heights range from 18" to 54" above grade.

Surface Mount, Soil Anchor, or Guardrail Post Type

- Multiple configurations with either flat top or round top to fit various applications.

Surface Mount Base Options

- Surface mount pin lock base
- Surface mount twist lock base
- Sub-level twist lock base
- Sub-surface twist lock base
- Portable base

Soil Anchor Options

- Open-end galvanized anchor
- Closed-end galvanized anchor
- 8", 14", 18", and 24" anchor lengths available for different soil conditions.

